

# FEV 2021


**PRODUCT RANGE**  
Recycled pellets



**DESPRIET GEBROEDERS NV**  
Looplife Polymers site  
B-2235 Hulshout, Belgium  
[www.looplife-polymers.eu](http://www.looplife-polymers.eu)

Type	Grade name	Color	MFI	Filters	Application	Origin	Regular	mT/month	Picture
PE-HD	r-HDPE-025-BK	Black	± 0,8 (190°C/2,16kg)	80 µm	Extrusion	Post-consumer	N	10	
PE-HD	r-HDPE03B-BK	Black	± 3 (190°C/2,16kg)	80 µm	Injection	Post-consumer	Y	20	
PE-HD	r-HDPE05B-DGY	Dark Grey	± 4 (190°C/2,16kg)	80 µm	Injection	Post-consumer	Y	150	
PE-HD	r-HDPE00-C3-IC	Black	± 0,3 (190°C/5 kg)	80 µm	Pipes	Pre-consumer	Y	50	
PE-HD	r-HDPE00-C3-TN	Black	± 0,3 (190°C/5 kg)	80 µm	Pipes	Pre-consumer	Y	10	
PE-HD	r-HDPE00A-BW-BK	Black	± 0,4 (190°C/5 kg)	80 µm	Blow	Pre-consumer	N	40	
PE-HD	r-HDPE00-ML-BK	Black	± 0,5 (190°C/5 kg)	80 µm	Extrusion	Post-industrial	Y	15	
PE-HD	r-HDPE00-SC-MX	Mix Grey	± 1 (190°C/5 kg)	80 µm	Extrusion	Pre-consumer	N	20	

<b>PE-HD</b>	r-HDPE00-W1-BK	Black	± 2 (190°C/5 kg)	80 µm	Blow	Post-industrial	N	66
<b>PE-HD</b>	r-HDPE01C-EBK	Black	± 3 (190°C/5 kg)	80 µm	Injection	Post-consumer	N	30
<b>PE-HD</b>	r-HDPE00C-GY	Medium Grey	± 3 (190°C/5 kg)	80 µm	Injection	Post-consumer	Y	100
<b>PE-HD</b>	r-HDPE01C-BK	Black	± 4 (190°C/5 kg)	80 µm	Injection	Post-consumer	N	100
<b>PE-HD</b>	r-HDPE02B-BR	Translucent Brown	± 5 (190°C/5kg)	80 µm	Film	Pre-consumer	Y	20
<b>PE-LLD</b>	r-LLDPE03A-GR	Medium Green	± 3 (190°C/2,16 kg)	80 µm	Rotomoulding	Post-industrial	Y	25
<b>PE-LLD</b>	r-LLDPE03A-BK	Black	± 3 (190°C/2,16 kg)	80 µm	Rotomoulding	Post-industrial	Y	25
<b>PP-H</b>	r-PP02B-RG-BK	Black	± 3 (230°C/2,16 kg)	80 µm	Extrusion	Pre-consumer	Y	20
<b>PP-H</b>	r-PP02A-FC	Black	± 4 (230°C/2,16 kg)	80 µm	Extrusion	Post-industrial	N	2
<b>PP-H</b>	r-PP02C-FC	Black	± 4 (230°C/2,16 kg)	80 µm	Extrusion	Post-industrial	N	2



<b>PP-H</b>	r-PP05B-RG-BK	Black	± 7 (230°C/2,16 kg)	80 µm	Extrusion	Pre-consumer	N	5
<b>PP-H</b>	r-PP05C-LP-BK	Black	± 5 (230°C/2,16 kg)	80 µm	Extrusion	Pre-consumer	N	17
<b>PP-H</b>	r-PP10C-MT-BK	Black	± 8 (230°C/2,16 kg)	80 µm	Injection	Pre-consumer	Y	25
<b>PP-H</b>	r-PP10B-RT-BK	Mix	± 10 (230°C/2,16 kg)	80 µm	Injection	Pre-consumer	Y	25
<b>PP-H</b>	r-PP20C-CG-BK	Black	± 20 (230°C/2,16 kg)	80 µm	Injection	Post-consumer	N	25
<b>PP-H</b>	r-PP25B-D-BK	Black	± 25 (230°C/2,16 kg)	80 µm	Injection	Pre-consumer	Y	10
<b>PP-H</b>	r-PP50B-D-DGY	Dark Grey	± 65 (230°C/2,16 kg)	80 µm	Injection	Pre-consumer	Y	10
<b>PE-PP</b>	r-PPPE20C-MX	Mix	± 20 (230°C/2,16 kg)	60 µm	Extrusion	Pre-consumer	N	24
<b>PE-PP</b>	r-PEPP03A-BK	Black	± 3 (190°C/2,16 kg)	60 µm	Extrusion	Pre-consumer	Y	50
<b>PE-PP</b>	r-PEPP03A-DG	Dark Green	± 3 (190°C/2,16 kg)	60 µm	Extrusion	Pre-consumer	Y	50

